Wall decoration

Water (eco) Solvent UVgel (mat)/UV Latex

IJM711 Wall Covering Silver Textileback FR 360 g/m²

Product Description

A premium fabric back vinyl coated wall covering with a fine textured silver surface. This wall covering product has a smooth Silver appearance, giving it a stunning effect. Making it the right choice for high-end retail, hotel and residential applications

Physical																					
	Weight		360 g	1/m ²	ISO 536		FR classification	B-s1,d0	EN 13501-1												
Properties	Thicknes	c.	460 μ		ISO 534																
					130 334																
	All values	listed are target	values																		
Applications/	Indoor w	all coverin	q		Durable and	was	hable														
features	Wall graphics Door coverage Interior decoration High end luxurious Wall Decoration				Easy application, Paste-the-wall No need to laminate Bio Pruf treated. Preventing growth of bacteria and mold CE-marking acc EN 15102:2007 +A1:2011																
																Flame Retarc	danc	:y: B -s1, d0 acco	ording to El	N 1305-1 pro	cedu
											Available										
											Available Widths (mm)	3"core		1372							
Refer for	Refer for our current offering to canon-europe.com/mediaguide																				
Storage Conditions	Shelf life: 1 year. Temperature 10-35°C, Relative Humidity 30-75% Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours before printing.																				
Print Conditions					5ºC and 35-70% n printer-type.	RH.															
Conditions Environment,	Optimal	print condi	itions may diff	fer fror				industrial v	vaste.												
Conditions Environment,	Optimal	print condi	itions may diff	fer fror quired	n printer-type.	and u		industrial v	vaste.												
Conditions Environment, Health & Safety	Optimal No Mater Cold	print condi rial Safety Warm	itions may diff Data Sheet red Hot	fer fror quired Cold:	n printer-type. . Handle waste a	and u ve	used material as	industrial v	vaste.												
Conditions Environment, Health & Safety Lamination	Optimal	print condi rial Safety	itions may diff Data Sheet re	fer fror quired Cold: Warm	n printer-type. . Handle waste a pressure sensitiv	and u ve I: 85'	used material as °C - 95°C	industrial v	vaste.												
Conditions Environment, Health & Safety Lamination	Optimal No Mater Cold no	print condi rial Safety Warm no	itions may diff Data Sheet red Hot No	fer fror quired Cold: Warm Hot: h	n printer-type. . Handle waste a pressure sensitiv n: heat activated	ve I: 85' 05°C	used material as °C - 95°C C -130°C	industrial v	vaste.												



Processing

Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. Load the media with care in the printers. Incorrect

loading can cause skewing or creasing. Use a takeup device to prevent wrinkling.

It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations. Canon Colour profiles include recommended settings for ink restrictions and printer parameters. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, in order to obtain the best results.

Application guidelines

Always pre-test the surface. The product has been used in many places under numerous possible conditions and has proven its reliability and performance.

The base surface should be carefully prepared: - Remove all old wallpaper (To remove the remains of old adhesives try using a squirting bottle with water and a few squirts of washing up liquid. This works perfectly on most wallpaper adhesives)

- Remove all remnants
- Smooth out any rough surfaces
- Clean with a damp cloth
- Prior to beginning all surfaces should be dry.

Adhesives

Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute. Washability

In general: Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing - certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Standard disclaimer: All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc. canon.com Canon Europe canon-europe.com English edition 0116 © Canon Europa N.V., 2020

