

HP Designjet T1200 Printer series

Achieve twice the productivity with two printers in one for medium-sized CAD/GIS workgroups.





Get more done in less time with fast setup, continuous printing and network sharing.

- Manage tight deadlines easily: print 2 A1-sized prints per minute using the Economode print setting
- Save time and paper with 2 online rolls and smart switching, enabling unattended printing
- Print continuously with reliable HP 300-ml matte black ink cartridges, a convenient front-loading top roll and media length tracking
- Print batch files² without opening any application thanks to the free HP Instant Printing Utility and embedded Web server
- Enjoy easy sharing with a built-in network card



Make a real impact with clear, accurate drawings and colourful presentations.

- Reach a new level of accuracy and professionalism: achieve fine lines, rich dark blacks, true neutral greys and a range of vivid colours with HP Vivera inks and the 6-ink printing system
- Achieve exacting detail with 0.02 mm minimum line width³ and highly precise drawings with 0.1% line accuracy
- Create great prints with new, improved HP bond papers and HP Recycled Bond Paper (100% recycled base paper)
- Optimise blue prints using the new printing mode for generic natural tracing paper

Print confidently with this reliable and secure solution

- Process complex files fast and accurately, with 32 GB of memory
- Free your network and workstation with reliable in-printer processing architecture
- Share this HP Designjet among authorised workgroups using built-in Gigabit Ethernet networking and Jetdirect support for secure IPsec and IPv6
- Secure disk erase and the external hard disk accessory⁴ provide even more security
- Do more with PostScript capabilities and experience greater operating system support with original HP-GL/2 and RTL























¹ With two rolls in one device, you achieve twice the productivity from a single printer.

 $^{2~\}mbox{HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, Powerpoint)}$

³ HP-GL/2 addressable

⁴ The 160 GB external hard disk drive accessory is an optional accessory; please purchase separately; this accessory is intended to replace the printer's internal hard disk as the repository of personal data, and can be removed from the printer and stored in a secure place

HP Designjet T1200 Printer series

TECHNICAL SPECIFICATIONS	
Print speed Line drawings	Fast: 28 sec/page, 103 A1 prints per hour
Printing	Tusi. 20 sec/ page, 100 AT pinns per nou
Print resolution	Up to 2400 x 1200 optimised dpi
Margins (top x bottom x left x right)	Roll: 5 mm (top), 5 mm (right), 5 mm (left), 5 mm (bottom)
Technology	Sheet: 5 mm (top), 5 mm (right), 5 mm (left), 16.75 mm (bottom) HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK), pigment-based (MK)
Ink colours	6 (cyan, grey, magenta, matte black, photo black, yellow)
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Line accuracy	+/- 0.1% (+/-0.1% of the specified vector length or +/-0.1 mm - whichever
	greater - at 23° C, 50-60% relative humidity, on A0 printing material in
Age to the state	Best or Normal mode with HP Matte Film)
Minimum line width Guaranteed minimum line width	0.02 mm (HP-GL/2 addressable)
Maximum print length	0.06 mm (ISO/IEC 13660:2001(E)) 91 m (OS and application dependent)
Image quality	71 III (O3 and application dependent)
Maximum optical density	2.15 maximum black optical density (6 L *min)
Media	
Handling	Sheet feed, two automatic roll feeds, automatic roll-switching, automatic
	cutter Clark Control of the Control
Types	Bond and coated paper, technical paper, film, photographic paper, backlit, self-adhesive
Weight	60 to 328 g/m²
Size	210 x 279 to 1118 x 1676 mm
Thickness	Up to 11.8 mil
Memory	
Standard	32 GB dedicated file-processing memory (384 MB RAM memory)
Hard disk	Standard, 160 GB
Connectivity	111:0 1100000 : 111:0 1100001 : 1100
Interfaces (standard)	1 Hi-Speed USB 2.0 Device port, 1 Hi-Speed USB 2.0 Host port, 1 EIO port, 1 Gigabit Ethernet (1000Base-T) port
Interfaces (optional)	HP Jetdirect internal print servers
Print languages (standard)	T1200 PS 1118 mm : Adobe® PostScript® 3, Adobe PDF 1.7, TIFF, JPEG,
3 3 (,	HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI; T1200 1118 mm: HP-GL/2,
	HP-RTL, CALS G4, HP PCL 3 GUI;
Drivers included	HP-GL/2, HP-RTL, Postscript drivers for Windows® (optimised for AutoCAD
	2000 and higher); HP PCL 3 GUI , Postscript drivers for Mac OS X and
	Linux; support for Citrix XenApp and Citrix XenServer environments). Postscript and Linux drivers only supported through CK834A.
Recommended system requirements	
Mac	Mac OS X v10.4, v10.5: PowerPC G4, G5, or Intel® Core Processor; 1
	GB RAM; 2 GB available hard disk space
Windows	Microsoft® Windows® XP Home/Professional (SP2 or higher): Intel®
	Pentium® family or AMD K6®/Athlon™/Duron™ family (1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista® Home
	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1
	GHz), 2 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	1770 700 1050
Printer	1770 x 722 x 1050 mm
Shipping Weight	1930 x 766 x 778 mm
Printer	86 kg
Shipping	115 kg
What's in the box	
CK834A	Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118
	mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif
CLIFOOA	PosterDesigner Pro for HP poster, start-up software, power cord
CH538A	Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif
	PosterDesigner Pro for HP poster, start-up software, power cord
Environmental ranges	
Operating Temperature	5 to 40° C
Recommended operating temperature	15 to 35° C (depending on paper type)
Storage temperature	-25 to 55° C
Recommended operating humidity	20 to 80% RH (depending on paper type)
Storage humidity Acoustic	0 to 95% RH
Sound Pressure	46 dB(A), 26 dB(A) (standby)
Sound Power	6.2 B(A), 4.4 B(A) (standby)
Power Consumption	
Maximum	120 watts maximum (active), $<$ 27 watts (standby), $<$ 7 watts $/$ $<$ 25 watts
	with embedded DFE (powersave), 0.1 watts (off)
Power requirements	Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3
Cartification	Hz), 2 A max
Certification Safety	EU (LVD and EN 60950-1 compliant), Russia (GOST)
Electromagnetic	Compliant with Class B requirements EU (EMC Directive)
Environmental	Energy Star, WEEE, EU RoHS, REACH, EuP, FEMP
ENERGY STAR	Yes
Warranty	
	Standard warranty: two years, next business day on site support. Warranty
	and support options vary by product, country and local legal requirements.

ORDERING INFORMATION

Product		
CK834A	HP Designjet T1200 1118 mm PostScript Printer	
CH538A	HP Designjet T1200 1118 mm Printer	
Accessories		
Q6709A	HP Designjet 44-inch Roll Feed Spindle	
CN501A	HP Designjet External Hard Disk	
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server	
CN088A	Serif PosterDesigner Software Pro for HP Designjet Printers	
CN454A	SCP reprocontrol for HP (1 printer)	
CN455A	SCP reprocontrol for HP (2 printers)	
Ink supplies		
C9397A	HP 72 69-ml Photo Black Ink Cartridge	
C9398A	HP 72 69-ml Cyan Ink Cartridge	
C9399A	HP 72 69-ml Magenta Ink Cartridge	
C9400A	HP 72 69-ml Yellow Ink Cartridge	
C9401A	HP 72 69-ml Grey Ink Cartridge	
C9403A	HP 72 130-ml Matte Black Ink Cartridge	
C9370A	HP 72 130-ml Photo Black Ink Cartridge	
C9371A	HP 72 130-ml Cyan Ink Cartridge	
C9372A	HP 72 130-ml Magenta Ink Cartridge	
C9373A	HP 72 130-ml Yellow Ink Cartridge	
C9374A	HP 72 130-ml Grey Ink Cartridge	
CH575A	HP 726 300-ml Matte Black Ink Cartridge	
C9380A	HP 72 Gray and Photo Black Printhead	
C9383A	HP 72 Magenta and Cyan Printhead	
C9384A	HP 72 Matte Black and Yellow Printhead	
Media supplies		
Q6628A	HP Super Heavyweight Plus Matte Paper-1067 mm x 30.5 m (42 in x 100 ft)	
C6030C	HP Heavyweight Coated Paper-914 mm x 30.5 m (36 in x 100 ft)	
C6020B	HP Coated Paper-914 mm x 45.7 m (36 in x 150 ft)	
C6036A	HP Bright White Inkjet Paper-914 mm x 45.7 m	
Q1397A	HP Universal Bond Paper-914 mm x 45.7 m (36 in x 150 ft)	
CG891A	HP Recycled Bond Paper-1067 mm x 45.7 m (42 in x 150 ft)	
C3868A	HP Natural Tracing Paper-914 mm x 45.7 m (36 in x 150 ft)	
C3875A	HP Clear Film-914 mm x 22.9 m (36 in x 75 ft)	
Q1426A	HP Universal High-gloss Photo Paper-610 mm x 30.5 m (24 in x 100 ft)	
Q1421A	HP Universal Semi-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)	
Service & support		

US235E HP Care Pack, Next Business Day On Site, 5 years
US236E HP Care Pack, Next Business Day On Site, 4 years
US237E HP Care Pack, Next Business Day On Site, 3 years
US230E HP Care Pack, 4hr 13x5 Same Business Day On Site, 3 years
US230E HP Care Pack, Post Warranty, Next Business Day On Site, 1 year
US23PE HP Care Pack, Post Warranty, Next Business Day On Site, 1 year

For more HP Large Format Media substrates and sizes please visit us online at: http://www.hp.com/go/designjet/supplies

For more information, visit our website at http://www.hp.com

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA2-8299 Published in EMEA October 2009

