

Fabiano Printmaking Rag 310gsm IFA 107

Product Description

Soft grain 100% cotton, matte finish, mould made digital fine art paper. Aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Soft Grain – Mould Made
- ✓ 100% Cotton Rag
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free - Archival

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios

Basic Weight (gsm)	310		
Paper Thickness (Microns)	565	Paper Thickness (Inches)	0.022
Base Material	100% Cotton		
Coating Type	Matte		
Surface Texture	Soft Grain 'Etching'		
Whiteness (CIE)	86		
Brightness (TAPPI)	97.3		
OBA Content	No		
pH	7.5		
Recyclable	Yes		
Print Settings*	MK Ink, a Textured Fine Art Paper setting is recommended as a starting point		
Notes			

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22", 36x48"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.