













MEDIATEX® Illuminance FR



	Einheit Unit	Norm Standard	Wert Value
Substrat Substrate		DIN 60001	100% Polyester 100% polyester
Bindung Weave		DIN ISO 9354	Gewebe woven fabric
Flächengewicht Weight	 g/m ²	DIN EN ISO 2286-2	120 ± 15
Brandverhalten Fire retardancy		B-s1,d0*, ÖNORM A3800	ja yes
Tintenart Type of ink		  	alle Solventtinten, UV-härt., Latextinten all kinds of solvent, UV-curable, latex inks
Anwendung Application			innen indoor
Breite Width	 cm inch	DIN EN ISO 2286-1	max. 510 max. 200,8
Druckseite Print side			Breite < 3m: Druckseite außen Breite > 3m: Druckseite innen width < 3m: print side outside width > 3m: print side inside
Rollenlänge Roll length	 m		40 - 150 ± 0,5

Anwendungen Applications



Leuchtkasten / lightbox, backlit
Rahmensysteme / framing systems
Spannsysteme / tensioning systems

Besonderheiten Characteristics

- höchste Druckqualität
highest print quality
- kein Farbbruch
no creasing colours
- kein Weißbruch
no white cracking / crazing
- wasserabweisend
water-repellent
- schmutzabweisend
dirt-repellent
- luftdicht
airproof
- kalt schneidbar
trimming cold
- homogene Oberfläche
homogenous surface

* erlaubt die Einstufung in die Kategorie M1 / permits the classification into the category M1

All details are nominal values and are subject to change within usual tolerances (± 5%). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 04/2019