



NON-WOVEN DESIGN2WALL UV 150

matt 2500, 150 g/m²

Economical non-woven wallpaper with a natural surface

The Non-woven design2wall UV 150 matt is an uncoated non-woven wallpaper for inkjet printing with latex and UV inks. This product is suitable for digital printing of wall decorations and wallpapers. It has a matt finished, natural surface and can be pasted without further surface protection, with standard non-woven wallpaper paste. It is flame retardant and certified.

Advantages

- High wet and dry strength
- Dry strippable
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1
- Hang using standard non-woven wallpaper paste



Technologies



Properties



General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

Physical data

Name	Value	Norm
Weight [g/m ²]	150	ISO 536
Thickness (paper) [µm]	320	ISO 534
ISO Brightness [%]	88	ISO 2470-1
Opacity [%]	90	ISO 2471
Tensile strength MD [N/15mm]	148	ISO 1924-3/2/300
Tensile strength CD [N/15mm]	94	ISO 1924-3/2/300
Wet tensile strength MD [N/15mm]	47	ISO 3781
Wet elongation CD (Fenchel) [%]	0.1	A 10-011/27
Water absorbency (Cobb) [g/m ²]	18	ISO 535

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.