



NON-WOVEN DESIGN2WALL SOL 195

matt 2512, 195 g/m²

High quality matt non-woven wallpaper for busy areas


The Non-woven design2wall Sol 195 matt is a high quality non-woven wallpaper for printing with solvent, latex and UV inks and is characterised by high colour brilliance and dimensional stability. It is flame retardant and certified. Due to the scratch resistance of the matt finish surface, this wallpaper is suitable for long-term use in busy areas.

Advantages

- Wide colour gamut and good colour rendition
- High opacity for good coverage of the underlying surface
- Good lightfastness
- Dimensionally stable, no wet or dry stretching
- Dry strippable
- Good coverage of uneven surfaces and cracks
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1
- Hang using standard non-woven wallpaper paste



Properties



General tips

To maintain the high quality of this fleece, it should be stored and converted in a climate of 30 – 65 % relative humidity and at temperatures of 10 – 30 °C (50 – 86 °F).

After pasting the wall with a standard wallpaper paste, the wallpaper can be hung just like all other fleece wallpapers. Thanks to its structure, it is easy to remove again and requires no additional protection.

Physical data

Name	Value	Norm
Weight [g/m ²]	195	ISO 536
Thickness (paper) [µm]	340	ISO 534
Whiteness, CIE D65/2°	75	ISO 11476
Opacity [%]	90	ISO 2471
Chromaticity (D65/10°)	L* 97 a* -0.5 b* 3.5	DIN 6174

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.