

XBFP250

Xativa Front Print Backlit Film



A heavyweight polyester based backlit film with excellent depth of colour great handleability and quick drying time.

Ideal for light boxes and illuminated displays.

Produce brilliant, razor sharp images no matter what the application. The microporous coating on the printable front side of this media enhances image definition and provides excellent colour contrast even without a backlight.

Its fast drying polyester based thick matt surface helps post processing run smooth by avoiding costly smudges and helps resist folds and creases. Furthermore is resistant to water penetration and is dimensionally stable after printing.

All specifications are correct at time of print and are subject to change without notice. E&OE

Product specifications

| Weight | 220 g/m ² DIN EN ISO536 | | | | | | | | | | | | |
|------------------------------------|---|-----------------|------------|------------|-------------|------------|--------------|------------|--------------|------------|--------------|------------|--------------|
| Thickness | 280 microns (+/- 11 microns) ISO534 | | | | | | | | | | | | |
| Opacity | > 36% ISO2471 | | | | | | | | | | | | |
| Whiteness | 115 (+/- 3%) ISO11475 | | | | | | | | | | | | |
| Finish | Matte | | | | | | | | | | | | |
| Water resistant | Good | | | | | | | | | | | | |
| Operating temperature | 15 to 100 degrees centigrade | | | | | | | | | | | | |
| Operating humidity | 20 to 80% RH | | | | | | | | | | | | |
| Dry time | Instant dry with heating (at 23 degrees centigrade, 50% RH) | | | | | | | | | | | | |
| Shelf time | 2 years, unopened in original packaging | | | | | | | | | | | | |
| Storage temperature | 0 to 40 degrees centigrade | | | | | | | | | | | | |
| Storage humidity | 5 to 95% RH | | | | | | | | | | | | |
| Country of origin | Product of United Kingdom | | | | | | | | | | | | |
| Printer / Ink Compatibility | Compatible with all aqueous based dye, pigment and UltraChrome K3 Inks from all leading manufacturers such as Canon, Epson and Hewlett Packard | | | | | | | | | | | | |
| Lamination | Can be laminated with commercially available thermal and pressure sensitive films | | | | | | | | | | | | |
| Ordering information | <table><thead><tr><th>Product numbers</th><th>Roll Sizes</th></tr></thead><tbody><tr><td>XBFP250-36</td><td>914mm x 30m</td></tr><tr><td>XBFP250-42</td><td>1067mm x 30m</td></tr><tr><td>XBFP250-50</td><td>1270mm x 30m</td></tr><tr><td>XBFP250-54</td><td>1372mm x 30m</td></tr><tr><td>XBFP250-60</td><td>1524mm x 30m</td></tr></tbody></table> | Product numbers | Roll Sizes | XBFP250-36 | 914mm x 30m | XBFP250-42 | 1067mm x 30m | XBFP250-50 | 1270mm x 30m | XBFP250-54 | 1372mm x 30m | XBFP250-60 | 1524mm x 30m |
| Product numbers | Roll Sizes | | | | | | | | | | | | |
| XBFP250-36 | 914mm x 30m | | | | | | | | | | | | |
| XBFP250-42 | 1067mm x 30m | | | | | | | | | | | | |
| XBFP250-50 | 1270mm x 30m | | | | | | | | | | | | |
| XBFP250-54 | 1372mm x 30m | | | | | | | | | | | | |
| XBFP250-60 | 1524mm x 30m | | | | | | | | | | | | |
| Warranty | Xativa large format printing materials are guaranteed to meet Xativa published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly | | | | | | | | | | | | |

