



A 230gsm matt coated paper giving brilliant colour reproduction, improved ink absorption and a short drying time.

Ideal for working comps, full colour renders, drawings with large flood fills and photo realistic prints

Streamline your workflow and maintain high productivity with this instant dry matt coated paper. Its special coating allows you to produce highly saturated prints with stunning colour reproduction and excellent detail without rippling. Its great handling properties also allows you to laminate immediately after printing.

And to help meet the the environmental objectives of your company and your clients this recyclable FSC certified paper supports responsible forest management worldwide.

All specifications are correct at time of print and are subject to change without notice. E&OE

Product specifications

Weight	229 g/m ² (+/- 20gsm) ISO536	
Thickness	290 microns (+/- 15 microns) ISO534	
Opacity	98% (+/-2%) DIN53146	
Whiteness	154 (+/- 4%) ISO11475	
Finish	Matt	
Shade	L	97 (+/- 1)
	a	4.0 (+/- 1)
	b	-14 (+/- 1)
Smoothness	19 (+/- 10s) (Bekk) ISO5627	
Stiffness md	89 (+/- 22mN) ISO2493	
Stiffness cd	46 (+/- 13mN) ISO2493	
Operating temperature	15 to 100 degrees centigrade	
Operating humidity	20 to 80% RH	
Dry time	Instant dry with heating (at 23 degrees centigrade, 50% RH)	
Shelf time	2 years, unopened in original packaging	
Storage temperature	0 to 40 degrees centigrade	
Storage humidity	5 to 95% RH	
Country of origin	Product of Germany	
Printer / Ink Compatibility	Compatible with all aqueous based dye, pigment and UltraChrome K3 Inks from all leading manufacturers such as Canon, Epson and Hewlett Packard	
Lamination	Can be laminated with commercially available thermal and pressure sensitive films	
Ordering information	Product numbers	Roll Sizes
	XXPMC230-A4	A4 x 80 sheets
	XXPMC230-A3	A3 x 100 sheets
	XXPMC230-A3+	A3+ x 100 sheets
	XXPMC230-17	432mm x 30m
	XXPMC230-17-3	432mm x 30m (3 inch core)
	XXPMC230-24	610mm x 30m
	XXPMC230-24-3	610mm x 30m (3 inch core)
	XXPMC230-36	914mm x 30m
	XXPMC230-42	1067mm x 30m
	XXPMC230-42-3	1067mm x 30m (3 inch core)
	XXPMC230-60	1524mm x 30m
Warranty	Xativa large format printing materials are guaranteed to meet Xativa published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly	



The mark of responsible forestry

